

THOROUGHCLEAN
WATER BLASTERS

D24M-50C-TO


PRESSURE CLEANER **Class B**

Diesel Driven - 24HP - MINE SPECIFICATION - 5075 PSI - Cold Water

5075 PSI

Max Pump Pressure
5000 PSI
Setup Pressure

YANMAR



Heavy Duty - DIESEL - Cold Water - 5075 PSI, 21 LPM

Heavy Duty Water Blasters - Portable, Skid, Trailer & Wash Bay Units



PH 1300 378 872
WEB www.trhc.com.au
EMAIL sales@trhc.com.au

24HP Heavy Duty Mine Spec, 1000L Poly Tank Trailer Mounted **DIESEL PRESSURE CLEANER**

The ideal trailer mounted water blaster that demands high pressure and/or flow in a rugged, tough and over-engineered machine, that will outlast any other water blaster!

MAX PUMP PSI 5075 PSI
STANDARD SETUP PSI 5000 PSI
FLOW/MINUTE 21 LPM

POWERED BY 24 HP YANMAR Diesel Engine
SIZE 445 x 185 x 165 cm
WEIGHT ~1000 kg

POWER SOURCE

- 24 HP YANMAR Water Cooled Diesel Engine.
- Push-button electric start
- Exhaust spark arrestor - AS certified.
- Close coupled drive via 2:1 gearbox.

DELIVERY

- Heavy duty glycerine-filled pressure gauge rated to 8,700 PSI.
- Heavy duty galvanized hose reel.

30m R2 thick wall 3/8" HP Hose:

- Rated to 5000 PSI.
- 4x burst rating.
- Hose end sleeved for operator protection.

Italian made dry gun with:

- 1200mm insulated stainless steel lance.
- Stainless steel fan nozzle.

PUMP

- **HAWK** PXi2135 Triplex Pump rated at 5075 PSI max @ 21 LPM.
- The pump is de-rated** to 5000 PSI to prolong pump life.
- Ceramic sleeved, stainless steel piston plunger rods and brass pump head.
- Low speed pump at 1450 RPM.

FRAME

- Heavy duty 4x4 style, fully hot dipped galvanised trailer.
- Land Cruiser style six stud wheels on 2-ton axle with spare wheel.
- Mechanical disk brakes with manual hand brake.
- LED side clearance lights and tail lights.
- Engine is vibration mounted on separate sub-frame.
- Stainless steel control box with hour meter & E-stop.

BY-PASS VALVE

- **VB60/600** by-pass valve. Zero PSI stored downstream when in by-pass.

MINE SPEC FEATURES

- Emergency-stop.
- Exhaust spark arrestor.
- Engine drip tray.
- 2.5kg Fire extinguisher.
- Wheel nut indicators.
- Wheel chocks mounted.
- Lockable battery isolator.
- Starter motor isolator.
- Covered battery box.
- Double wire insulation.
- Anderson type jump-start receptacle.

SUPPLY

- Water supply is from onboard 1000L water tank, dual water intake with dual water filters to protect the pump from water debris.
- Tank with float switch to shut motor down on low water supply - protects pump against cavitation & dry running - extending pump life.

ANALYSIS - DESIGN - CONSTRUCTION - ACCESSORIES

DISCLAIMER All images are a representation only and are not to scale. Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, due to ongoing product development and improvements, products may vary from this data sheet. The user of the information agrees that the information is subject to change without notice.

**Derating (or de-rating or de-tuning) is the operation of a machine at less than its rated maximum power in order to prolong its life. The term is commonly applied to [electrical](#) and [electronic devices](#) and to [internal combustion engines](#)