

# D7R-1.7-SF

FIRE FIGHTING SKID

Diesel Driven - 6.7HP - RENTAL SPEC - 140 PSI MPP

### 140 PSI Max Pump Pressure











Heavy Duty - DIESEL - 140 PSI, 0 - 400 LPM

Heavy Duty Water Blasters - Portable, Skid, Trailer & Wash Bay Units



PH 1300 378 872 WEB www.trhc.com.au EMAIL sales@trhc.com.au

# 6.7HP Heavy Duty Rental Spec, 1000 litre IBC Skid Mounted DIESEL FIRE FIGHTER

The ideal skid mounted fire fighter that demands high pressure and/or flow in a rugged, tough and over-engineered machine, that will outlast any other fire fighting unit!

MAX PUMP PSI 140 PSI FLOW/MINUTE 0 - 400 LPM

POWERED BY 6.7HP YANMAR Engine SIZE 235 x 125 x 140 cm WEIGHT ~350 kg

#### **POWER SOURCE**

- YANMAR L70N diesel, electric start engine.
- Compact, Direct Injection Technology.
- Close coupled direct drive.
- Ball bearing supported crankshaft for greater stability.
- Automatic mechanical de-compression system.
- Stainless steel control box with:
  - Emergency stop
  - Hour meter
  - On / Off control

#### **PUMP**

- DAVEY Fire Fighting Pump with twin impellers, self-priming.
- Pump casing, diffusers and impellers manufactured from quality corrosion resistant marine grade aluminium for long life.
- 4 Way discharge port for easy installation with a choice of plumbing sizes.
- Low oil protection.

#### **FRAME**

- Fully hot dipped galvanised steel frame.
- Engine is vibration mounted on separate sub-frame.
- Forkliftable via builtin skids, or via four AS certified D-shackle lifting lugs.

#### **SUPPLY AND DELIVERY**

- Water supply is from onboard 1000 litre IBC water tank.
- 5 meters 1 ½" pool/ dam suction hose, with strainer.
- Heavy duty galvanized hose reel (Lockable during travel).

## 30m AS Certified 1" Fire Fighting Hose:

- Rated to 300 PSI.
- Adjustable brass nozzle.



### ANALYSIS - DESIGN - CONSTRUCTION - ACCESSORIES

DISCLAIMER All images are a representation only and are not to scale. Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, due to ongoing product development and improvements, products may vary from this data sheet. The user of the information agrees that the information is subject to change without notice.