

THOROUGHCLEAN
WATER BLASTERS

E10I-36C

PRESSURE CLEANER

Electric Driven - 10HP - INDUSTRIAL SPEC - 3625 PSI MPP - Cold Water

3625 PSI

Max Pump Pressure
2700 PSI
Setup Pressure

Ravel



Heavy Duty - ELECTRIC - Cold Water - 3625 PSI, 18LPM

Heavy Duty Water Blasters - Portable, Skid, Trailer & Wash Bay Units



PH 1300 378 872
WEB www.trhc.com.au
EMAIL sales@trhc.com.au

10HP Heavy Duty, Industrial Spec Portable ELECTRIC PRESSURE CLEANER

The ideal portable water blaster that demands high pressure and/or flow in a rugged, tough and over-engineered machine, that will outlast any other water blaster!

MAX PUMP PSI 3625 PSI

STANDARD SETUP PSI 2700 PSI

FLOW/MINUTE 18 LPM

POWERED BY 10HP Electric Motor

POWER SOURCE

- Italian heavy duty 10HP (7.5kW) electric motor - class 'F' wound.
- 415 volt, three-phase.
- 8 meters of 20 Amp lead with 20Amp
- DOL motor starter, in stainless steel control box.

DELIVERY

- Heavy duty glycerine-filled pressure gauge rated to 8,700 PSI.

10m R2 thick wall 3/8" HP Hose:

- Rated to 5000 PSI.
- 4x burst rating.
- Hose end sleeved for operator protection.

Italian made dry gun with:

- 900mm insulated stainless steel lance.
- Stainless steel fan nozzle.

PUMP

- **HAWK** NPM1825R Triplex Pump rated at 3625 psi max @ 18 LPM.
- The pump is de-rated** to 2700 PSI to prolong pump life.
- Ceramic sleeved, stainless steel piston plunger rods and brass pump head.
- Low speed pump at 1450 RPM.

FRAME

- Fully hot dipped galvanised steel frame.
- 'Flat free' wheels for easy rolling over uneven surfaces.

BY-PASS VALVE

- Pulsar Zero 35 by-pass valve. Zero PSI stored downstream when in by-pass.

SUPPLY

- Water supply is via an over-sized industrial water filter to protect the pump from water line debris.
- Pneumatic accumulator to prevent pressure spikes & water hammering.
- **STAINLESS** steel water break tank with float switch to shut motor down on load water supply - Protect pumps against cavitation & dry running - extended pump life



**Derating (or de-rating or de-tuning) is the operation of a machine at less than its rated maximum power in order to prolong its life. The term is commonly applied to [electrical](#) and [electronic devices](#) and to [internal combustion engines](#)

ANALYSIS - DESIGN - CONSTRUCTION - ACCESSORIES

DISCLAIMER All images are a representation only and are not to scale. Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, due to ongoing product development and improvements, products may vary from this data sheet. The user of the information agrees that the information is subject to change without notice.