

**THOROUGH**CLEAN****  
WATER BLASTERS

# E10R-36C

## PRESSURE CLEANER

Electric Driven - 10HP - RENTAL SPEC - 3625 PSI MPP - Cold Water

**3625 PSI**

Max Pump Pressure

**2800 PSI**

Setup Pressure

7kW Motor



Heavy Duty - ELECTRIC - Cold Water - 3625 PSI, 18LPM

Heavy Duty Water Blasters - Portable, Skid, Trailer & Wash Bay Units



PH 1300 378 872  
WEB [www.trhc.com.au](http://www.trhc.com.au)  
EMAIL [sales@trhc.com.au](mailto:sales@trhc.com.au)

# 10HP Heavy Duty, Rental Spec Portable ELECTRIC PRESSURE CLEANER

The ideal portable water blaster that demands high pressure and/or flow in a rugged, tough and over-engineered machine, that will outlast any other water blaster!

**MAX PUMP PSI** 3625 PSI  
**STANDARD SETUP PSI** 2800 PSI  
**FLOW/MINUTE** 18 LPM

**POWERED BY** 10 HP Electric Motor  
**SIZE** 95 x 80 x 80 cm  
**WEIGHT** ~160 kg

## POWER SOURCE

- Italian heavy duty 10HP (7kW) electric motor - class 'F' wound.
- 415 volt, three-phase.
- DOL motor starter, in stainless steel control box.
- Timed shutdown.
- Wired to shut down on low tank water level - preventing pump from cavitating and running dry.
- 10m lead with 20 Amp plug.

## DELIVERY

- Heavy duty glycerine-filled pressure gauge rated to 10,000 PSI.
- Heavy duty galvanized hose reel.

**30m R2 thick wall 3/8"**

**HP Hose:**

- Rated to 5000 PSI.
- 4x burst rating.
- Hose end sleeved for operator protection.

**Italian made dry gun with:**

- 900mm insulated stainless steel lance.
- Stainless steel fan

## PUMP

- **HAWK** NPM1825 Triplex Pump rated at 3625 PSI max @ 18 LPM.
- The pump is de-rated\*\* to 2800 PSI to prolong pump life.
- Ceramic sleeved, stainless steel piston plunger rods and brass pump head.
- Low speed pump at 1450 RPM.

## FRAME

- Fully hot dipped galvanised steel frame.
- Extra-large 'flat free' wheels for easy rolling over uneven surfaces.

## BY-PASS VALVE

- K7-2 by-pass valve. Zero PSI stored downstream when in by-pass.
- No pressure stored in high pressure line when machine is turned off.

## SUPPLY

- Water supply is via an industrial water filter to protect the pump from water line debris.
- The pump is protected by automatic low water shutdown tank.
- Pneumatic accumulator to prevent pressure spikes & water hammering.



\*\*Derating (or de-rating or de-tuning) is the operation of a machine at less than its rated maximum power in order to prolong its life. The term is commonly applied to [electrical](#) and [electronic devices](#) and to [internal combustion engines](#)

## ANALYSIS - DESIGN - CONSTRUCTION - ACCESSORIES

**DISCLAIMER** All images are a representation only and are not to scale. Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, due to ongoing product development and improvements, products may vary from this data sheet. The user of the information agrees that the information is subject to change without notice.