

THOROUGHCLEAN
WATER BLASTERS

P20R-43C-T

PRESSURE CLEANER

Petrol Driven - 20HP - RENTAL SPECIFICATION - 4350 PSI MPP - Cold Water

4350 PSI

Max Pump Pressure

4000 PSI

Setup Pressure

HONDA



Heavy Duty - PETROL - Cold Water - 4000 PSI, 18 LPM

Heavy Duty Water Blasters - Portable, Skid, Trailer & Wash Bay Units



PH 1300 378 872

WEB www.trhc.com.au

EMAIL sales@trhc.com.au

20HP Heavy Duty Rental Spec, 1000 litre IBC Trailer Mounted PETROL PRESSURE CLEANER

The ideal trailer mounted water blaster that demands high pressure and/or flow in a rugged, tough and over-engineered machine, that will outlast any other water blaster!

MAX PUMP PSI 4350 PSI
STANDARD SETUP PSI 4000 PSI
FLOW/MINUTE 18 LPM

POWERED BY 20HP Class Honda Engine

POWER SOURCE

- Genuine Honda GX630 electric start engine.
- Close coupled direct drive via 2:1 gearbox.
- Ball bearing supported crankshaft for greater stability.
- Automatic mechanical de-compression system.
- OHV design for increased efficiency and optimal power transfer.

DELIVERY

- Heavy duty glycerine-filled pressure gauge rated to 10,000 PSI.
- Heavy duty galvanized hose reel.

30m R2 thick wall 3/8"

HP Hose:

- Rated to 5000 PSI.
- 4x burst rating.
- Hose end sleeved for operator protection.

Italian made dry gun with:

- 900mm insulated stainless steel lance.
- Stainless steel fan nozzle.

PUMP

- **HAWK** XLT1830 Triplex Pump rated at 4350 PSI max @ 18 LPM.
- The pump is de-rated** to 4000 PSI to prolong pump life.
- Ceramic sleeved, stainless steel piston plunger rods and brass pump head.
- Low speed pump at 1450 RPM.

FRAME

- Heavy duty 4x4 style, fully hot dipped galvanised trailer.
- Land Cruiser style six stud wheels on 2-ton axle with spare wheel.
- Mechanical disk brakes with manual hand brake.
- LED side clearance lights and tail lights.
- Engine is vibration mounted on separate sub-frame.

BY-PASS VALVE

- Pulsar Zero PSI stored downstream when in by-pass.

SUPPLY

- Water supply is from onboard 1000L water tank, dual water intake with dual water filters to protect the pump from water debris.
- Tank with float switch to shut motor down on low water supply - protects pump against cavitation & dry running - extending pump life.



ANALYSIS - DESIGN - CONSTRUCTION - ACCESSORIES

DISCLAIMER All images are a representation only and are not to scale. Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, due to ongoing product development and improvements, products may vary from this data sheet. The user of the information agrees that the information is subject to change without notice.

**Derating (or de-rating or de-tuning) is the operation of a machine at less than its rated maximum power in order to prolong its life. The term is commonly applied to [electrical](#) and [electronic devices](#) and to [internal combustion engines](#)