

P20R-43C-TO PRESSURE CLEANER

Petrol Driven - 20HP - RENTAL SPECIFICATION - 4350 PSI MPP - Cold Water

4350 PSI Max Pump Pressure 3400 PSI Setup Pressure

HONDA







12 Ashburn Rd, Bundamba, QLD 4304 PH 07 5467 2025 WEB www.thoroughclean.com.au EMAIL sales@thoroughclean.com.au

Heavy Duty - PETROL - Cold Water - 4350 PSI, 22 LPM

Heavy Duty Water Blasters - Portable, Skid, Trailer & Wash Bay Units

20HP Heavy Duty Rental Spec, 1200 litre Poly Trailer Mounted PETROL PRESSURE CLEANER

The ideal trailer mounted water blaster that demands high pressure and/or flow in a rugged, tough and over-engineered machine, that will outlast any other water blaster!

MAX PUMP PSI 4350 PSI STANDARD SETUP PSI 3400 PSI FLOW/MINUTE 22 LPM

POWER SOURCE

- Genuine Honda GX630 electric start engine.
- Close coupled direct drive via 2:1 gearbox.
- Ball bearing supported crankshaft for greater stability.
- Automatic mechanical de-compression system.
- OHV design for increased efficiency and optimal power transfer.

DELIVERY

- Heavy duty glycerinefilled pressure gauge rated to 10,000 PSI.
- Heavy duty galvanized hose reel.
 20m P2 thick wall 2 /9"

30m R2 thick wall 3/8" HP Hose:

- Rated to 5000 PSI.
- 4x burst rating.
- Hose end sleeved for operator protection.
 Italian made dry gun

with:

- 900mm insulated stainless steel lance.
- Stainless steel fan nozzle.

PUMP

- HAWK XLT1830 Triplex Pump rated at 4350 PSI max @ 22 LPM.
- The pump is de-rated** to 3400 PSI to prolong pump life.
- Ceramic sleeved, stainless steel piston plunger rods and brass pump head.
- LubeBuddy tripling the oil supply to the pump.
- Low speed pump at 1450 RPM.

FRAME

- Heavy duty 4x4 style, fully hot dipped galvanised trailer.
- Land Cruiser style wheels on 2-ton axle with spare wheel.
- Mechanical disk brakes with manual hand brake.
- LED side clearance lights.
- Engine is vibration mounted on separate sub-frame.

BY-PASS VALVE

WEIGHT ~700 ka

• Worlds best soft acting low to high PSI by-pass valve. Zero PSI stored downstream when in by-pass - protects hose/ gun assembly.

SIZE 360 x 185 x 180 cm

POWERED BY 20HP Honda Engine

• Soft-acting gun protects against pressure spikes and saves seals.

SUPPLY

- Water supply is from onboard 1200L water tank, dual water intake with dual water filters to protect the pump from water debris.
- Tank with float switch to shut motor down on low water supply protects pump against cavitation & dry running - extending pump life.



**Derating (or de-rating or de-tuning) is the operation of a machine at less than its rated maximum power in order to prolong its life. The term is commonly applied to electrical and electronic devices and to internal combustion engines

ANALYSIS - DESIGN - CONSTRUCTION - ACCESSORIES

DISCLAIMER All images are a representation only and are not to scale. Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, due to ongoing product development and improvements, products may vary from this data sheet. The user of the information agrees that the information is subject to change without notice.