

P20R-50C PRESSURE CLEANER

Petrol Driven - 20HP - RENTAL SPEC - 5075 PSI MPP - Cold Water (Class B)

5075 PSI Max Pump Pressure 4800 PSI Setup Pressure

Honda





Heavy Duty - PETROL - Cold Water - 5075 PSI, 17 LPM

Heavy Duty Water Blasters - Portable, Skid, Trailer & Wash Bay Units



PH 1300 378 872 WEB www.trhc.com.au EMAIL sales@trhc.com.au

20HP Heavy Duty, RENTAL Spec Portable PETROL PRESSURE CLEANER

The ideal portable water blaster that demands high pressure and/or flow in a rugged, tough and over-engineered machine, that will outlast any other water blaster!

MAX PUMP PSI 5075 PSI STANDARD SETUP PSI 4800 PSI FLOW/MINUTE 17 LPM

POWER SOURCE

- Genuine Honda V-twin GX690 electric start engine.
- Close coupled direct drive via 2:1 gearbox.
- Ball bearing supported crankshaft for greater stability.
- OHV design for increased efficiency and optimal power transfer.

DELIVERY

- Heavy duty glycerinefilled pressure gauge rated to 10,000 PSI.
 30m R2 thick wall 3/8" HP Hose:
- Rated to 5000 PSI.
- 4x burst rating.
- Hose end sleeved for operator protection. Italian made dry gun with:
- 1200mm insulated stainless steel lance.
- Stainless steel fan nozzle.

PUMP

- HAWK PXi1735 Triplex Pump rated at 5075 PSI max @ 17 LPM.
- The pump is de-rated** to 4800 PSI to prolong pump life.
- Ceramic sleeved, stainless steel piston plunger rods and brass pump head.
- Thermoshield to dump water over 63°C.
- Low speed pump at 1450 RPM.

FRAME

- Fully hot dipped galvanised frame.
- Hose reel integrated into frame.
- Stainless steel 22 litre fuel tank.
- Extra-large 'flat free' wheels for easy rolling over uneven surfaces.



**Derating (or de-rating or de-tuning) is the operation of a machine at less than its rated maximum power in order to prolong its life. The term is commonly applied to electrical and electronic devices and to internal combustion engines

ANALYSIS - DESIGN - CONSTRUCTION - ACCESSORIES

DISCLAIMER All images are a representation only and are not to scale. Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, due to ongoing product development and improvements, products may vary from this data sheet. The user of the information agrees that the information is subject to change without notice.

POWERED BY 20HP Class Honda Engine SIZE 125 x 85 x 95cm WEIGHT ~160 kg

BY-PASS VALVE

• High quality soft acting low to high PSI by-pass valve. Zero PSI stored downstream when in by-pass.

SUPPLY

- Water supply is via an over-sized industrial water filter to protect the pump from water line debris.
- Stainless steel header tank with low water shut down