

THOROUGHCLEAN
WATER BLASTERS

WASHMATE 15R-43C

WASH-BAY PRESSURE CLEANER

Electric Driven - 15HP - RENTAL SPEC - 4350 PSI MPP - Cold Water

4350 PSI

Max Pump Pressure

3400 PSI

Setup Pressure

TecnoMec



Heavy Duty - ELECTRIC - Cold Water - 4350 PSI, 22 LPM

Heavy Duty Water Blasters - Portable, Skid, Trailer & Wash Bay Units



PH 1300 378 872
WEB www.trhc.com.au
EMAIL sales@trhc.com.au

15HP Heavy Duty, Rental Spec Wash-Bay ELECTRIC PRESSURE CLEANER

The ideal wash-bay water blaster that demands high pressure and/or flow in a rugged, tough and over-engineered machine, that will outlast any other water blaster!

MAX PUMP PSI 4350 PSI
STANDARD SETUP PSI 3400 PSI
FLOW/MINUTE 22 LPM

POWERED BY 15 HP Electric Motor
SIZE 68 x 57 x 150 cm
WEIGHT ~230 kg

POWER SOURCE

- Italian heavy duty 15 HP (11kW) electric motor - class 'F' wound.
- 415 volt, three-phase.
- DOL motor starter, in stainless steel control box.
- Timed shutdown.
- Wired to shut down on low tank water level - preventing pump from cavitating and running dry.

DELIVERY

- Heavy duty glycerine-filled pressure gauge rated to 10,000 PSI.
- Heavy duty galvanized hose reel.

30m R2 thick wall 3/8" HP Hose:

- Rated to 5000 PSI.
- 4x burst rating.
- Hose end sleeved for operator protection.

Italian made dry gun with:

- 900mm insulated stainless steel lance.
- Stainless steel fan nozzle.

PUMP

- **HAWK** XLT2230 Triplex Pump rated at 4350 PSI max @ 22 LPM.
- The pump is de-rated** to 3000 - 3400 PSI to prolong pump life.
- Ceramic sleeved, stainless steel piston plunger rods and brass pump head.
- Low speed pump at 1450 RPM.

FRAME

- Fully hot dipped galvanised steel frame.
- Vibration mounted control box with hour meter.

BY-PASS VALVE

- Pulse Zero valve.

SUPPLY

- Water supply is via an over-sized industrial water filter to protect the pump from water line debris.
- Stainless steel water break tank with float switch to shut motor down on low water supply - protects pump against cavitation & dry running - extending pump life.
- Pneumatic accumulator to prevent pressure spikes & water hammering.



ANALYSIS - DESIGN - CONSTRUCTION - ACCESSORIES

DISCLAIMER All images are a representation only and are not to scale. Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, due to ongoing product development and improvements, products may vary from this data sheet. The user of the information agrees that the information is subject to change without notice.

**Derating (or de-rating or de-tuning) is the operation of a machine at less than its rated maximum power in order to prolong its life. The term is commonly applied to [electrical](#) and [electronic devices](#) and to [internal combustion engines](#)