

THOROUGHCLEAN

WATER BLASTERS

P13R-36C-TO

PRESSURE CLEANER

Petrol Driven - 13HP - RENTAL SPECIFICATION - 3625 PSI - Cold Water

3625 PSI

Max Pump Pressure
3000 PSI
Setup Pressure

HONDA



Heavy Duty - PETROL - Cold Water - 3625 PSI, 18LPM

Heavy Duty Water Blasters - Portable, Skid, Trailer & Wash Bay Units



PH 1300 378 872
WEB www.trhc.com.au
EMAIL sales@trhc.com.au

13HP Heavy Duty Rental Spec, 1000 litre Oval Poly Tank Trailer Mounted **PETROL PRESSURE CLEANER**

The ideal trailer mounted water blaster that demands high pressure and/or flow in a rugged, tough and over-engineered machine, that will outlast any other water blaster!

MAX PUMP PSI 3625 PSI
STANDARD SETUP PSI 3000 PSI
FLOW/MINUTE 18 LPM

POWERED BY 13HP Class Honda Engine
SIZE 450 x 185 x 165cm
WEIGHT ~750 kgs

POWER SOURCE

- Genuine Honda GX390 recoil start engine.
- Close coupled direct drive via 2:1 gearbox.
- Ball bearing supported crankshaft for greater stability.
- Automatic mechanical de-compression system.
- OHV design for increased efficiency and optimal power transfer.

DELIVERY

- Heavy duty glycerine-filled pressure gauge rated to 8,700 PSI.
- Heavy duty galvanized hose reel.

30m R2 thick wall 3/8"

HP Hose:

- Rated to 5000 PSI.
- 4x burst rating.
- Hose end sleeved for operator protection.

Italian made dry gun with:

- 900mm insulated stainless steel lance.
- Stainless steel fan nozzle.

PUMP

- **HAWK** NPM1825 Triplex Pump rated at 3625 PSI max @ 18LPM.
- The pump is de-rated** to 3000 PSI to prolong pump life.
- Ceramic sleeved, stainless steel piston plunger rods and brass pump head.
- Low speed pump at 1450 RPM.

FRAME

- Heavy duty 4x4 style, fully hot dipped galvanised trailer.
- Land Cruiser style six stud wheels on 2-ton axle with spare wheel.
- Mechanical disk brakes with manual hand brake.
- LED side clearance lights and tail lights.
- Engine is vibration mounted on separate sub-frame.

BY-PASS VALVE

- K1 by-pass valve. Zero PSI stored downstream when in by-pass.

SUPPLY

- Water supply is from onboard 1000L water tank, dual water intake with dual water filters to protect the pump from water debris.
- Tank with float switch to shut motor down on low water supply - protects pump against cavitation & dry running - extending pump life.



ANALYSIS - DESIGN - CONSTRUCTION - ACCESSORIES

DISCLAIMER All images are a representation only and are not to scale. Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, due to ongoing product development and improvements, products may vary from this data sheet. The user of the information agrees that the information is subject to change without notice.

**Derating (or de-rating or de-tuning) is the operation of a machine at less than its rated maximum power in order to prolong its life. The term is commonly applied to [electrical](#) and [electronic devices](#) and to [internal combustion engines](#)