

THOROUGHCLEAN
WATER BLASTERS

P20D-43C

PRESSURE CLEANER

Petrol Driven - 20HP - INDUSTRIAL SPEC - 4350 PSI MPP - Cold Water

4350 PSI

Max Pump Pressure

4000 PSI

Setup Pressure

Ducar



Heavy Duty - PETROL - Cold Water - 4350 PSI, 18 LPM

Heavy Duty Water Blasters - Portable, Skid, Trailer & Wash Bay Units



PH 1300 378 872

WEB www.trhc.com.au

EMAIL sales@trhc.com.au

20HP Heavy Duty, Industrial Spec Portable PETROL PRESSURE CLEANER

The ideal portable water blaster that demands high pressure and/or flow in a rugged, tough and over-engineered machine, that will outlast any other water blaster!

MAX PUMP PSI 4350 PSI
STANDARD SETUP PSI 4000 PSI
FLOW/MINUTE 18 LPM

POWERED BY 20 HP Ducar Engine

POWER SOURCE

- Genuine Ducar V-twin DHT720E electric start engine.
- Close coupled direct drive via 2:1 gearbox.
- Ball bearing supported crankshaft for greater stability.
- OHV design for increased efficiency and optimal power transfer.

DELIVERY

- Heavy duty glycerine-filled pressure gauge rated to 10,000 PSI.

20m R2 thick wall 3/8" HP Hose:

- Rated to 5000 PSI.
- 4x burst rating.
- Hose end sleeved for operator protection.

Italian made dry gun with:

- 900mm insulated stainless steel lance.
- Stainless steel fan nozzle.

PUMP

- **HAWK** XLT1830 Triplex Pump rated at 4350 PSI max @ 18 LPM.
- The pump is de-rated** to 4000 PSI to prolong pump life.
- Ceramic sleeved, stainless steel piston plunger rods and brass pump head.
- Thermoshield to dump water over 63°C.
- Low speed pump at 1450 RPM.

FRAME

- Fully hot dipped galvanised frame.
- Hose rack integrated into frame.
- Stainless steel 22 litre fuel tank
- Extra-large 'flat free' wheels for easy rolling over uneven surfaces.

BY-PASS VALVE

- V680/280 by-pass valve.

SUPPLY

- Water supply is via an industrial water filter to protect the pump from water line debris. Stainless steel water tank



DISCLAIMER All images are a representation only and are not to scale. Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, due to ongoing product development and improvements, products may vary from this data sheet. The user of the information agrees that the information is subject to change without notice.

ANALYSIS - DESIGN - CONSTRUCTION - ACCESSORIES

**Derating (or de-rating or de-tuning) is the operation of a machine at less than its rated maximum power in order to prolong its life. The term is commonly applied to [electrical](#) and [electronic devices](#) and to [internal combustion engines](#)