

THOROUGHCLEAN
WATER BLASTERS

P20R-50C-BB

PRESSURE CLEANER

Class B

Petrol Driven - 22HP - RENTAL SPECIFICATION - 5075 PSI MPP - Cold Water

5000 PSI

Max Pump Pressure

5000 PSI

Setup Pressure

HONDA



Heavy Duty - PETROL - Cold Water - 5075 PSI, 17 LPM

Heavy Duty Water Blasters - Portable, Skid, Trailer & Wash Bay Units



PH 1300 378 872

WEB www.trhc.com.au

EMAIL sales@trhc.com.au

22HP Heavy Duty Rental Spec, 1000 litre Skid Mounted **PETROL PRESSURE CLEANER**

The ideal skid mounted water blaster that demands high pressure and/or flow in a rugged, tough and over-engineered machine, that will outlast any other water blaster!

MAX PUMP PSI 5000 PSI
STANDARD SETUP PSI 5000 PSI
FLOW/MINUTE 17 LPM

POWERED BY 20 HP HONDA Petrol Engine
SIZE 220 x 130 x 138 cm
WEIGHT ~350 kg

POWER SOURCE

- Genuine Honda GX630 electric start engine.
- Close coupled direct drive via 2:1 gearbox.
- Ball bearing supported crankshaft for greater stability.
- Automatic mechanical de-compression system.
- OHV design for increased efficiency and optimal power transfer.

DELIVERY

- Heavy duty glycerine-filled pressure gauge rated to 10,000 PSI.
- Heavy duty galvanized hose reel (Lockable during travel).

30m R2 thick wall 3/8" HP Hose:

- Rated to 5000 PSI.
- 4x burst rating.
- Hose end sleeved for operator protection.

Italian made dry gun with:

- 1200mm insulated stainless steel lance.
- Stainless steel fan nozzle.

PUMP

- **HAWK** PXi1735 Triplex Pump rated at 5075 PSI max @ 17 LPM.
- The pump is de-rated** to 5000 PSI to prolong pump life.
- Ceramic sleeved, stainless steel piston plunger rods and brass pump head.
- Low speed pump at 1450 RPM.

FRAME

- Fully hot dipped galvanised steel frame.
- Engine is vibration mounted on separate sub-frame.
- Forkliftable via built-in skids.

BY-PASS VALVE

- VB60/600

SUPPLY

- Water supply is from onboard 1000L water tank, dual water intake with dual water filters to protect the pump from water debris.
- Tank with float switch to shut motor down on low water supply - protects pump against cavitation & dry running - extending pump life.



ANALYSIS - DESIGN - CONSTRUCTION - ACCESSORIES

DISCLAIMER All images are a representation only and are not to scale. Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, due to ongoing product development and improvements, products may vary from this data sheet. The user of the information agrees that the information is subject to change without notice.

Derating (or de-rating or de-tuning) is the operation of a machine at less than its rated maximum power in order to prolong its life. The term is commonly applied to **electrical and **electronic devices** and to **internal combustion engines**