

P6R-1.7-TFO

FIRE FIGHTING TRAILER

Petrol Driven - 6.5HP - RENTAL SPEC - 165 PSI MPP

165 PSI Max Pump Pressure











Heavy Duty - PETROL - 165 PSI, 0 - 400 LPM

Heavy Duty Water Blasters - Portable, Skid, Trailer & Wash Bay Units



PH 1300 378 873 WEB www.trhc.com.au EMAIL sales@trhc.com.au

6.5HP Heavy Duty Rental Spec, 1000L Poly Tank Trailer Mounted PETROL FIRE FIGHTER

The ideal trailer mounted fire fighter that demands high pressure and/or flow in a rugged, tough and over-engineered machine, that will outlast any other fire fighting unit!

MAX PUMP PSI 165 PSI FLOW/MINUTE 0 - 400 LPM

POWERED BY 6.5HP Class Honda Engine SIZE 410 x 185 x 180 cm

POWER SOURCE

- Genuine Honda GX200 recoil start engine.
- Close coupled direct drive.
- Ball bearing supported crankshaft for greater stability.
- Automatic mechanical de-compression system.
- OHV design for increased efficiency and optimal power transfer.

PUMP

- DAVEY Fire Fighting Pump with twin impellers, self-priming.
- Pump casing, diffusers and impellers manufactured from quality corrosion resistant marine grade aluminium for long life.
- 4 Way discharge port for easy installation with a choice of plumbing sizes.

FRAME

- Heavy duty 4x4 style, fully hot dipped galvanised trailer.
- Land Cruiser style six stud wheels on 2-ton axle with spare wheel.
- ADR approved mechanical disk brakes with manual hand brake.
- ADR approved LED side clearance lights.
- ADR approved LED tail lights.
- Engine is vibration mounted on separate sub-frame.

SUPPLY AND DELIVERY

- Water supply is from onboard 1000 litre red poly water tank.
- 5 meters 1 ½" pool/ dam suction hose, with strainer.
- Heavy duty galvanized hose reel (Lockable during travel).

30m AS Certified 1" Fire Fighting Hose:

- Rated to 300 PSI.
- Adjustable brass nozzle.



ANALYSIS - DESIGN - CONSTRUCTION - ACCESSORIES

DISCLAIMER All images are a representation only and are not to scale. Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, due to ongoing product development and improvements, products may vary from this data sheet. The user of the information agrees that the information is subject to change without notice.