

THOROUGHCLEAN

WATER BLASTERS *Over-engineered — On purpose*

D10M-36C

PRESSURE CLEANER

Diesel Driven - 10HP - MINE SPECIFICATION - 3625 PSI MPP - Cold Water

3625 PSI

Max Pump Pressure

3000 PSI

Setup Pressure

YANMAR



12 Ashburn Rd, Bundamba, QLD 4304

PH 07 5467 2025

WEB www.thoroughclean.com.au

EMAIL sales@thoroughclean.com.au

Heavy Duty - DIESEL - Cold Water - 3625 PSI, 15LPM

Heavy Duty Water Blasters - Portable, Skid, Trailer & Wash Bay Units

10HP Heavy Duty Mine Spec Portable DIESEL PRESSURE CLEANER

The ideal portable water blaster that demands high pressure and/or flow in a rugged, tough and over-engineered machine, that will outlast any other water blaster!

MAX PUMP PSI 3625 PSI
STANDARD SETUP PSI 3000 PSI
FLOW/MINUTE 15 LPM

POWERED BY 10 HP YANMAR Diesel Engine
SIZE 95 x 80 x 80 cm
WEIGHT ~190 kg

POWER SOURCE

- 10 HP YANMAR Air Cooled Diesel Engine.
- Push-button electric start
- Exhaust spark arrestor - AS certified.
- Wired to shut down on low tank water level - preventing pump from cavitating and running dry.
- Close coupled direct drive via 2:1 gearbox.

DELIVERY

- Heavy duty glycerine-filled pressure gauge rated to 10,000 PSI.
- Heavy duty galvanized hose reel.

30m R2 thick wall 3/8" HP Hose:

- Rated to 5000 PSI.
- 4x burst rating.
- Hose end sleeved for operator protection.

Italian made dry gun with:

- 900mm insulated stainless steel lance.
- Stainless steel fan nozzle.

PUMP

- **HAWK** NPM1525R Triplex Pump rated at 3625 PSI max @ 15 LPM.
- The pump is de-rated** to 3000 PSI to prolong pump life.
- Ceramic sleeved, stainless steel piston plunger rods and brass pump head.
- *LubeBuddy* - tripling the oil supply to the pump.
- Low speed pump at 1450 RPM.

FRAME

- Fully hot dipped galvanised steel frame.
- Engine is vibration mounted on separate sub-frame.
- Stainless steel control box with hour meter & E-stop.
- Extra-large 'flat free' wheels for easy rolling over uneven surfaces.

BY-PASS VALVE

- Worlds best soft acting low to high PSI by-pass valve. Zero PSI stored downstream when in by-pass - protects hose/gun assembly.
- Soft-acting gun protects against pressure spikes and saves seals.

MINE SPEC FEATURES

- Emergency-stop.
- Exhaust spark arrestor.
- Engine drip tray.
- Lockable battery isolator.
- Covered battery terminals.
- Double wire insulation.

SUPPLY

- Water supply is via an over-sized industrial water filter to protect the pump from water line debris.
- *AquaTech* - Pressurised water break tank with float switch to shut motor down on low water supply - protects pump against cavitation & dry running - extending pump life.



**Derating (or de-rating or de-tuning) is the operation of a machine at less than its rated maximum power in order to prolong its life. The term is commonly applied to [electrical](#) and [electronic devices](#) and to [internal combustion engines](#)

ANALYSIS - DESIGN - CONSTRUCTION - ACCESSORIES

DISCLAIMER All images are a representation only and are not to scale. Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, due to ongoing product development and improvements, products may vary from this data sheet. The user of the information agrees that the information is subject to change without notice.