

# **THOROUGHCLEAN**

**WATER BLASTERS** *Over-engineered — On purpose*

## **E15R-30H**

### **PRESSURE CLEANER**

Electric Driven - 15HP - RENTAL SPEC - 4350 PSI MPP - Hot Water

**4350 PSI**

Max Pump Pressure

**3000**

Setup Pressure



WORLD LEADER IN  
INDUSTRIAL, HEAVY-DUTY,  
MULTI-PLUNGER PUMPS



12 Ashburn Rd, Bundamba, QLD 4304

**PH** 07 5467 2025

**WEB** [www.thoroughclean.com.au](http://www.thoroughclean.com.au)

**EMAIL** [sales@thoroughclean.com.au](mailto:sales@thoroughclean.com.au)

**Heavy Duty - ELECTRIC - Hot Water - 4350 PSI, 22 LPM**

**Heavy Duty Water Blasters - Portable, Skid, Trailer & Wash Bay Units**

**15HP****ELECTRIC PRESSURE CLEANER**

The ideal wash-bay water blaster that demands high pressure and/or flow in a rugged, tough and over-engineered machine, that will outlast any other water blaster!

**MAX PUMP PSI** 4350 PSI**STANDARD SETUP PSI** 3000 PSI**FLOW/MINUTE** 22 LPM**POWERED BY** 15 HP WEG Electric Motor**SIZE** 130 x 80 x 170 cm**WEIGHT** ~350 kg**POWER SOURCE**

- WEG heavy duty 15 HP (11kW) electric motor - class 'H' wound.
- 415 volt, three-phase.
- Star-Delta soft starter, in stainless steel control box.

**POWER SUPPLY:**

- Requires 32A C-Curve Circuit Breaker **OR** 20A D-Curve Circuit Breaker.

**DELIVERY**

- Heavy duty glycerine-filled pressure gauge rated to 10,000 PSI.
- Heavy duty galvanized hose reel.

**30m R2 thick wall 3/8" HP Hose:**

- Rated to 5000 PSI.
- 4x burst rating.
- Hose end sleeved for operator protection.

**Italian made dry gun with:**

- 900mm insulated stainless steel lance.
- Stainless steel fan nozzle.
- Pneumatic accumulator to absorb pressure spikes.

**PUMP**

- **HAWK** XLT2230 Triplex Pump rated at 3000PSI max @ 22 LPM.
- Ceramic sleeved, stainless steel piston plunger rods and brass pump head.
- *LubeBuddy* - tripling the oil supply to the pump.
- Low speed pump at 1450 RPM.

**FRAME**

- Fully hot dipped galvanised steel frame.
- Vibration mounted control box with hour meter.

**BY-PASS VALVE**

- Worlds best soft acting low to high PSI by-pass valve. Zero PSI stored downstream when in by-pass - protects hose/gun assembly.
- Soft-acting gun protects against pressure spikes and saves seals.

**BOILER / BURNER**

- **HEAVY** duty horizontal boiler with 1/2" mild steel coils, set to **70°C**.
- 70 litre stainless steel fuel tank to boiler.
- Oversized CAV296 fuel filter.

**SUPPLY**

- Water supply is via dual over-sized industrial water filters to protect the pump from water line debris.
- Built-in water break tank with float switch to shut motor down on low water supply - protects pump against cavitation & dry running - extending pump life.

**AUTOMATIC ENGINE SHUT-DOWNS:**

- Low water supply.
- Low oil to pump.
- Low fuel.
- Timed by-pass shutdown.
- Pump oil over temp.

\*\*Derating (or de-rating or de-tuning) is the operation of a machine at less than its rated maximum power in order to prolong its life. The term is commonly applied to **electrical** and **electronic devices** and to **internal combustion engines**

**ANALYSIS - DESIGN - CONSTRUCTION - ACCESSORIES**

**DISCLAIMER** All images are a representation only and are not to scale. Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, due to ongoing product development and improvements, products may vary from this data sheet. The user of the information agrees that the information is subject to change without notice.