

THOROUGHCLEAN
WATER BLASTERS *Over-engineered — On purpose*

WASHMATE 10R-36C

WASH-BAY PRESSURE CLEANER

Electric Driven - 10HP - RENTAL SPEC - 3000 PSI MPP - Cold Water

3000 PSI

Max Pump Pressure

2800 PSI

Setup Pressure

TecnoMec



12 Ashburn Rd, Bundamba, QLD 4304

PH 1300 378 872

WEB www.thoroughclean.com.au

EMAIL sales@thoroughclean.com.au

Heavy Duty - ELECTRIC - Cold Water - 3000 PSI, 18 LPM

Heavy Duty Water Blasters - Portable, Skid, Trailer & Wash Bay Units

10HP Heavy Duty, Rental Spec Wash-Bay ELECTRIC PRESSURE CLEANER

The ideal wash-bay water blaster that demands high pressure and/or flow in a rugged, tough and over-engineered machine, that will outlast any other water blaster!

MAX PUMP PSI 3000 PSI
STANDARD SETUP PSI 2800 PSI
FLOW/MINUTE 18 LPM

POWERED BY 10 HP TecnoMec Electric Motor
SIZE 68 x 57 x 150 cm
WEIGHT ~200 kg

POWER SOURCE

- Italian heavy duty 10 HP (7.5kW) electric motor - class 'F' wound.
- 415 volt, three-phase.
- DOL motor starter, in stainless steel control box.
- Timed shutdown.
- Wired to shut down on low tank water level - preventing pump from cavitating and running dry.

DELIVERY

- Heavy duty glycerine-filled pressure gauge rated to 10,000 PSI.
- Heavy duty galvanized hose reel.

30m R2 thick wall 3/8" HP Hose:

- Rated to 5000 PSI.
- 4x burst rating.
- Hose end sleeved for operator protection.

Italian made dry gun with:

- 900mm insulated stainless steel lance.
- Stainless steel fan nozzle.

PUMP

- **HAWK** NPM 1825 Triplex Pump rated at 3000 PSI max @ 18 LPM.
- The pump is de-rated** to 2800 PSI to prolong pump life.
- Ceramic sleeved, stainless steel piston plunger rods and brass pump head.
- Lube Buddy - tripling the oil supply to the pump.
- Low speed pump at 1450 RPM.

FRAME

- Fully hot dipped galvanised steel frame.
- Vibration mounted control box with hour meter.

BY-PASS VALVE

- Worlds best soft acting low to high PSI by-pass valve. Zero PSI stored downstream when in by-pass - protects hose/gun assembly.
- Soft-acting gun protects against pressure spikes and saves seals.

SUPPLY

- Water supply is via an over-sized industrial water filter to protect the pump from water line debris.
- Stainless steel water break tank with float switch to shut motor down on low water supply - protects pump against cavitation & dry running - extending pump life.
- Pneumatic accumulator to prevent pressure spikes & water hammering.



**Derating (or de-rating or de-tuning) is the operation of a machine at less than its rated maximum power in order to prolong its life. The term is commonly applied to [electrical](#) and [electronic devices](#) and to [internal combustion engines](#)

ANALYSIS - DESIGN - CONSTRUCTION - ACCESSORIES

DISCLAIMER All images are a representation only and are not to scale. Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, due to ongoing product development and improvements, products may vary from this data sheet. The user of the information agrees that the information is subject to change without notice.